

# EstrichBoy

## DC 260/45, DC 260/55



### For semi-dry floor screeds

- Cement screed
- Calcium sulphate screed (anhydrite)
- Magnesia screed
- Vibrating floors (consistency-dependent)



### The tried and tested classic – available again!

The EstrichBoy from Putzmeister – advancement and unrivalled configuration options.

The new development focussed on user-friendliness, durability and ease of servicing. The new EstrichBoy is convincing up to the last detail.

- Reliable, robust and easy to operate
- User-friendly by ergonomic control panel
- High delivery rate, improved efficiency
- Extra Power (as option): 
- Of lasting value and economical thanks to the high resale value
- Top class service with wide dealer service network
- Training for users and engineers in our Academy



BRINKMANN



Lifting eye for transport by lorry or on the construction site



New revised operating concept: The operator can view and set all the necessary information directly from the control panel.



The innovative canopy concept and the removable rear section allow easy access to all important service and maintenance points

## Further benefits:

- **Technology „made in Germany“**
- **Optimized accessibility and ground clearance**
- **Low maintenance and wear-resistant**
- **Flexible application possibilities**
- **Choose "your" machine with a wide variety of equipment options**
- **High delivery rate, improved efficiency**

Technical data	DC 260/45	DC 260/55
Mixer drum	260 l, 200 l useful capacity	
Delivery range*	180 m horizontal, 90 m vertical	
Delivery rate (theo.)*	3.8–5.2 m³/h	4.0–5.2 m³/h
Delivery pressure	8 bar	
Compressor	4.3 m³/min	4.8 m³/min
Drive motor	3 cylinder Deutz Diesel with turbocharger, 36.4 kW (Stage V and 3A available)	3 cylinder Deutz Diesel with turbocharger, 44.5 kW (Stage V and 3A available)
Weight	1,715 kg / 1,840 kg (B) / 1,900 kg (BS)	
Length × width × height	5067 × 1525 × 1840 mm (Standard) 5210 × 1525 × 2526 mm (B + BS)	
Filling height	820 mm (Standard), 400 mm (B + BS)	
Chassis	Braked, manual brake adjustment, approval up to 80 km/h Optionally extendable to 100 km/h	
Mixer	hydraulically driven, incl. reverse and overload protection	
Maximum particle size	16 mm	

Equipment	DC 260/45	DC 260/55
Car coupling	■	■
Lifting eye	■	■
Light holder 12 V	■	■
Manual lid	■	■
Radio remote control (BS version)	■	■
Vessel outlet, center	■	■
Software package	■	■
Central lubrication system	■	■
Conversion to 100 km/h	■	■
Customer labelling	■	■
High pressure cleaner	■	■
Light holder 24 V	■	■
Location system	■	■
Protective plate for feeder	■	■
Software package	■	■
Special canopy paint (standard orange)	■	■
Straight tailpipe with flap	■	■
Styrofoam hopper	■	■
Support feet (kettle)	■	■
Toolbox	■	■
Truck coupling	■	■
Water dosing	on request	
Wear plates (6 mm )	■	■
Wear plates (Hardox 8 mm )	■	■
Wear plates at the dome	■	■
Wear plates impact protection (both sides)	■	■
Working lights (12 Volt)	■	■

\* The data is based on experience and depends on the material properties.

■ Series ■ Optional

BRINKMANN  
 A brand of the Putzmeister Group  
 Max-Eyth-Straße 10 · 72631 Aichtal  
 Tel. +49 (7127) 599-0 · Fax +49 (7127) 599-743  
 info@estrichboy.de · www.estrichboy.de

