



Putzmeister

Your advantages

- Easy to transport
- Material hopper simple to clean
- Worm parts quick to change according to each application
- Ideal for renovation and repair specialists with small work crews

P 12 – mixing, pumping and spraying



The P 12 really does have everything you need to help you to complete small jobs quickly and profitably. The compact machine combines three functions: It can mix, pump or spray – and changing between functions just requires the flip of a switch.

Example of filling frames – Here, the mixing quality and manageability are particularly important. The P 12 masters these both perfectly.

Example of injecting and setting anchors – Here, you can use the P 12 to perfectly fill the drill holes and fix the anchors.

Example of fire protection mortar – When cable fire breaks or pipe shafts are being sealed, speed is of the essence, as fire protection mortar sets within a very short space of time. The P 12 mixes the fire protection mortar to the optimum quality. These are just three of many ways you can use the P 12.

Your competent Putzmeister dealer will be happy to advise you on technical details and application issues.

Plaster/Fine plaster

- Cementitious adhesive and reinforcement mortar
- Spray plaster
- Textured plaster
- Fine plaster
- Levelling compound



Special applications

- Fire protection mortar
- Wet mortar
- ETICS
- High mixing quality for joint and frame mortar
- For injecting and anchoring with or without pressure



Mixing, pumping and spraying from a single material hopper



Discharge connection with pressure gauge for connecting mortar hoses



Practical accessories for a range of applications

Technical data

P 12

| | |
|------------------------------------|--------------------------------------|
| Mixer drum | 50 l |
| Delivery rate (theor.)* | 6 – 12 l/min |
| Delivery pressure | 25 bar |
| Delivery range** | 30 m horizontal, 15 m vertical |
| Worm pump | D5 short |
| Engine | 1.4 kW at 94 rpm / 1.8 kW at 188 rpm |
| Power supply (CE connector) | 400 V / 50 Hz + 60 Hz, 16 A, 5p, 6h |
| Weight | 125 kg |
| Length × width × height | 714 × 696 × 1437 mm |
| Filling height | 939 mm |
| Pressure connection | M 35 |
| Maximum particle size | 4 mm |

* The delivery rate is theoretical and depends on the pump pressure.

** The data is based on experience and depends on the material properties.

Equipment

| | |
|---|---|
| Cable remote control 20 m | ■ |
| Cleaning tool | ■ |
| Instruction manual and spare parts list | ■ |
| Seal ring for mortar coupling | ■ |
| Standard tool | ■ |
| Water connection Geka V25-40 | ■ |
| Auxiliary compressor | □ |
| Pneumatic remote control | □ |

□ Optional ■ Standard

Putzmeister Mörtelmaschinen GmbH

Max-Eyth-Straße 10 · 72631 Aichtal / Germany
 P.O.Box 2152 · 72629 Aichtal / Germany
 Tel. +49 7127 599-0 · Fax +49 7127 599-743
 mm@putzmeister.com · www.putzmeister.com

